



HINO200

SERIES

A Toyota Group Company



315 NAC





A Toyota Group Company

200 SERIES



L I G H T & C O N V E N I E N T

SPECIFICATIONS

RANGE / SERIES	HINO 200
MODEL NAME	315 NAC
DRIVE SYSTEM	4 x 2 (4W)
ENGINE	
Model	TOYOTA 1GD-FTV
Max. Output PS rpm	144 3,400
Max. Torque N.m rpm	300 1,200 - 3,200
Emission Standard	Euro 4
Max. Engine Speed (rpm)	4,400
Type	Diesel, Variable Nozzle Turbocharger & Intercooled (VNT), 4-Cycle, Vertical, Inline, 4-Cylinder, Double Overhead Camshaft (DOHC), Water-cooled
Combustion System	Compression Ignition, 4-Stroke
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	2.755
Fuel Tank Capacity (L)	60
TRANSMISSION	
Type	5-Speed M/T with Overdrive
PERFORMANCE	
Max. Speed (kph)	130
BRAKES	
Service (Type) (Features)	Dual-Circuit, Hydraulic, Vacuum Assist Front: Disc Brake , Rear: Drum Brake with Auto Brakeshoe Adjuster
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft
WHEELS & TIRES	
Tire Size	195/70R15 195/75R15 (Opt.)
SUSPENSIONS	
Front	Double Wishbone, Independent Torsion Bar Springs with Double Acting Shock Absorbers and Stabilizer Bar
Rear	Semi-Elliptic Main and Auxiliary Leaf Springs and Rubber Rebound Bumpers with Double Acting Shock Absorbers
SAFETY & OTHER AMENITIES	
Cab Airconditioning	N/A
Power Door & Window	N/A
Anti-lock Brake System (ABS)	Optional
Vehicle Stability Control (VSC)	Optional
SRS Airbag (Driver)	Optional
DIMENSIONS & WEIGHTS	
Wheelbase (mm)	2,545
Length (mm)	4,595
Width (mm)	1,695
Height (mm)	2,030
Gross Vehicle Weight (Kg)	3,490



- Aluminum Van
- Dropside Cargo

- Other Body Option :
- Utility Van



Fast delivery lead time on select units
with standard Hino Quality Body



TOYOTA GROUP
QUALITY