



HINO

# HINO200

SERIES

A Toyota Group Company



315





A Toyota Group Company

# 200

**SERIES**



L I G H T & C O N V E N I E N T

## SPECIFICATIONS

<b>RANGE / SERIES</b>	<b>HINO 200</b>
<b>MODEL NAME</b>	<b>315</b>
<b>DRIVE SYSTEM</b>	<b>4 x 2 (4W)</b>
<b>ENGINE</b>	
Model	TOYOTA 1GD-FTV
Max. Output PS   rpm	144   3,400
Max. Torque N.m   rpm	300   1,200 - 3,200
Emission Standard	Euro 4
Max. Engine Speed (rpm)	4,400
Type	Diesel, Variable Nozzle Turbocharger & Intercooled (VNT), 4-Cycle, Vertical, In-line, 4-Cylinder, Double Overhead Camshaft (DOHC), Water-cooled
Combustion System	Compression Ignition, 4-Stroke
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	2.755
Fuel Tank Capacity (L)	80
<b>TRANSMISSION</b>	
Type	5-Speed M/T with Overdrive
<b>PERFORMANCE</b>	
Max. Speed (kph)	130
<b>BRAKES</b>	
Service (Type) (Features)	Dual-Circuit, Hydraulic, Vacuum Assist Front: <b>Disc Brake</b> , Rear: Drum Brake with Auto Brakeshoe Adjuster
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft
<b>WHEELS &amp; TIRES</b>	
Tire Size	195/70R15   195/75R15 (Opt.)
<b>SUSPENSIONS</b>	
Front	Double Wishbone, Independent Torsion Bar Springs with Double Acting Shock Absorbers and Stabilizer Bar
Rear	Semi-Elliptic Main and Auxiliary Leaf Springs and Rubber Rebound Bumpers with Double Acting Shock Absorbers
<b>SAFETY &amp; OTHER AMENITIES</b>	
Cab Airconditioning	Equipped
Power Door & Window	Equipped
Anti-lock Brake System (ABS)	Optional
Vehicle Stability Control (VSC)	Optional
SRS Airbag (Driver)	Optional
<b>DIMENSIONS &amp; WEIGHTS</b>	
Wheelbase (mm)	2,545
Length (mm)	4,595
Width (mm)	1,695
Height (mm)	2,030
Gross Vehicle Weight (Kg)	3,490

**HINO**  
QUALITY BODY

- Aluminum Van
- Dropside Cargo

Other Body Option :  
- Utility Van



Fast delivery lead time on select units  
with standard Hino Quality Body



TOYOTA GROUP  
QUALITY