



HINO

HINO500

SERIES

A Toyota Group Company



1625 | 1625 Long



A Toyota Group Company

MEDIUM-DUTY
500
SERIES



RANGE / SERIES	HINO 500	
MODEL NAME	1625	1625 Long
MODEL CODE	FG8JJ7A	FG8JP7A
DRIVE SYSTEM	4 x 2 (6W)	
GROSS VEHICLE WEIGHT (Kg)	16,000	
GROSS COMBINATION MASS (Kg)	N/A	
TRANSMISSION	6-Speed M/T with Overdrive	
TIRES & RIMS	11R22.5-16PR	
FUEL TANK CAPACITY (L)	200	
DIMENSIONS		
Wheelbase (mm)	4,330	5,530
Length (mm)	7,785	9,485
Width (mm)	2,490	
Height (mm)	2,750	2,745
ENGINE		
Model	J08E-WF	
Emission Standard	Euro 4	
Max. Engine Speed (rpm)	2,600	
Type	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, In-line, 6-Cylinder, Overhead Camshaft, Water-cooled	
Combustion System	Direct Injection Type	
Fuel Injection System	Electronic Control Common Rail Type	
Displacement (L)	7.684	
PERFORMANCE		
Max. Output (PS) ISO Net JIS Gross	240 245	
Max. Torque (Nm) ISO Net JIS Gross	716 726	
Max. Speed (kph)	104	
SUSPENSION		
Front	Semi-elliptic Tapered Leaf Springs (Reinforced Type) with Double Acting Shock Absorbers and Stabilizer Bar	Semi-elliptic Tapered Leaf Springs (Reinforced Type) with Double Acting Shock Absorbers
Rear	Semi-elliptic Main and Auxiliary Leaf Springs (Reinforced Type)	
BRAKES		
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type, Equipped with ABS	
(Features)	Leading and Trailing Shoes for Front and Rear Wheels	
Parking	Air-operated Spring Brake Acting on Rear Axle	